FHLRY

105°C, 600/900V



Construction
Conductor: Flexible Bare Copper or Flexible Tinned Copper
Insulation: Extruded · PVC

Thermal Characteristics
Operating Temperature: 105°C

Electrical Characteristics
Operating Voltage: 600/900V

Application
Automotive High-Voltage Circuits: Ultra-thin-wall primary wiring for high-voltage automotive circuits.

General Characteristics
Ultra-Thin Wall: Ultra-thin insulation keeps the finished cable small for dense, lightweight harnesses.
Fluid Resistance: Resists gasoline, diesel and engine oil in vehicle service.

Standards & Approvals
ISO 19642-5: High-voltage single-core cables for automobiles.
ISO 6722-1: Test methods for single-core automotive cables.

FHLRY-A

CASMO Part No.	Conductor				Min. Ins. Thickness (mm)	Max. Overall O.D. (mm)	Max. DCR @20°C (Ω/km)		Nom. Cable Weight (kg/km)
	Conductor Size (mm²)	No. Of Strands	Max. Strand Dia. (mm)	Max. Conductor Dia. (mm)			BC	TPC	
1150380.35/7-**-XX	0.35	7	0.27	0.80	0.20	1.40	54.4	55.5	4.7
1150380.5/19-**-XX	0.5	19	0.19	1.00	0.22	1.60	37.1	38.2	6.2
1150380.75/19-**-XX	0.75	19	0.24	1.20	0.24	1.90	24.7	25.4	9.2
1150381/19-**-XX	1	19	0.27	1.35	0.24	2.10	18.5	19.1	12.0
1150381.5/19-**-XX	1.5	19	0.33	1.70	0.24	2.40	12.7	13	16.7
1150382.5/19-**-XX	2.5	19	0.41	2.20	0.28	3.00	7.6	7.82	27.1

Table Notes

† Part No. code: XX = colour code — BK Black, WH White, RD Red, GN Green, BN Brown, BL Blue, OR Orange, YW Yellow, VT Violet, GY Grey, PK Pink, TN Tan, CL Clear.

‡ Replace ** with the conductor code: AS for bare copper or TS for tinned copper.

FHLRY-B

CASMO Part No.	Conductor				Min. Ins. Thickness (mm)	Max. Overall O.D. (mm)	Max. DCR @20°C (Ω/km)		Nom. Cable Weight (kg/km)
	Conductor Size (mm²)	No. Of Strands	Max. Strand Dia. (mm)	Max. Conductor Dia. (mm)			BC	TPC	
1150380.35/12-**-XX	0.35	12	0.21	0.90	0.20	1.40	54.4	55.5	4.6
1150380.5/16-**-XX	0.5	16	0.21	1.00	0.22	1.60	37.1	38.2	6.6
1150380.75/24-**-XX	0.75	24	0.21	1.20	0.24	1.90	24.7	25.4	9.1
1150381/32-**-XX	1	32	0.21	1.35	0.24	2.10	18.5	19.1	12.1
1150381.5/30-**-XX	1.5	30	0.26	1.70	0.24	2.40	12.7	13	16.9

Please confirm application-specific requirements with CASMO before ordering. Specifications are subject to change; please ensure you are using the latest revision.

© CASMO CABLE LLC. All rights reserved.

FHLRY

105°C, 600/900V



FHLRY-B

CASMO Part No.	Conductor				Min. Ins. Thickness (mm)	Max. Overall O.D. (mm)	Max. DCR @20°C (Ω/km)		Nom. Cable Weight (kg/km)
	Conductor Size (mm²)	No. Of Strands	Max. Strand Dia. (mm)	Max. Conductor Dia. (mm)			BC	TPC	
1150382/28-**-XX	2	28	0.31	2.00	0.28	2.80	9.42	9.69	22.4
1150382.5/50-**-XX	2.5	50	0.26	2.20	0.28	3.00	7.6	7.82	27.9
1150384/56-**-XX	4	56	0.31	2.75	0.32	3.70	4.71	4.85	44.6
1150386/84-**-XX	6	84	0.31	3.30	0.32	4.30	3.14	3.23	65.6

Table Notes

† Part No. code: XX = colour code — BK Black, WH White, RD Red, GN Green, BN Brown, BL Blue, OR Orange, YW Yellow, VT Violet, GY Grey, PK Pink, TN Tan, CL Clear.

‡ Replace ** with the conductor code: AS for bare copper or TS for tinned copper.

Please confirm application-specific requirements with CASMO before ordering. Specifications are subject to change; please ensure you are using the latest revision.

© CASMO CABLE LLC. All rights reserved.