FLRYW125

125°C, 25/60V



Construction
Conductor: Flexible Bare Copper or Flexible Tinned Copper
Insulation: Extruded · Heat-Resistant PVC

Thermal Characteristics
Operating Temperature: 125°C

Electrical Characteristics
Operating Voltage: 25/60V

Application
Automotive Low-Voltage Circuits: Heat-resistant thin-wall primary wiring for low-voltage automotive circuits.

General Characteristics
Thin-Wall Construction: Thin insulation keeps the harness bundle smaller and lighter.
Heat Stability: Holds its dimensions after heat exposure, with minimal shrinkage at the cable ends.

Standards & Approvals
ISO 19642-3: Low-voltage single-core cables for automobiles.
ISO 6722-1: Test methods for single-core automotive cables.

FLRYW125-A

CASMO Part No.	Conductor				Min. Ins. Thickness (mm)	Max. Overall O.D. (mm)	Max. DCR @20°C (Ω/km)		Nom. Cable Weight (kg/km)
	Conductor Size (mm²)	No. Of Strands	Max. Strand Dia. (mm)	Max. Conductor Dia. (mm)			BC	TPC	
1150060.13/7-**-XX	0.13	7	0.16	0.50	0.20	1.05	136	140	2.1
1150060.22/7-**-XX	0.22	7	0.21	0.70	0.20	1.20	84.8	86.5	3.1
1150060.35/7-**-XX	0.35	7	0.26	0.80	0.20	1.30	54.4	55.5	4.6
1150060.5/19-**-XX	0.5	19	0.19	1.00	0.22	1.60	37.1	38.2	6.5
1150060.75/19-**-XX	0.75	19	0.24	1.20	0.24	1.90	24.7	25.4	9.2
1150061/19-**-XX	1	19	0.26	1.35	0.24	2.10	18.5	19.1	12.1
1150061.5/19-**-XX	1.5	19	0.32	1.70	0.24	2.40	12.7	13	16.9
1150062.5/19-**-XX	2.5	19	0.41	2.20	0.28	3.00	7.6	7.82	27.5

Table Notes

† Part No. code: XX = colour code — BK Black, WH White, RD Red, GN Green, BN Brown, BL Blue, OR Orange, YW Yellow, VT Violet, GY Grey, PK Pink, TN Tan, CL Clear.

‡ Replace ** with the conductor code: AS for bare copper or TS for tinned copper.

FLRYW125-B

CASMO Part No.	Conductor				Min. Ins. Thickness (mm)	Max. Overall O.D. (mm)	Max. DCR @20°C (Ω/km)		Nom. Cable Weight (kg/km)
	Conductor Size (mm²)	No. Of Strands	Max. Strand Dia. (mm)	Max. Conductor Dia. (mm)			BC	TPC	
1150060.35/12-**-XX	0.35	12	0.21	0.90	0.20	1.40	54.4	55.5	4.5
1150060.5/16-**-XX	0.5	16	0.21	1.00	0.22	1.60	37.1	38.2	6.7

Please confirm application-specific requirements with CASMO before ordering. Specifications are subject to change; please ensure you are using the latest revision.

© CASMO CABLE LLC. All rights reserved.

casmocable
CABLES FOR EXTREMES

FLRYW125

125°C, 25/60V



FLRYW125-B

CASMO Part No.	Conductor				Min. Ins. Thickness (mm)	Max. Overall O.D. (mm)	Max. DCR @20°C (Ω/km)		Nom. Cable Weight (kg/km)
	Conductor Size (mm²)	No. Of Strands	Max. Strand Dia. (mm)	Max. Conductor Dia. (mm)			BC	TPC	
1150060.75/24-**-XX	0.75	24	0.21	1.20	0.24	1.90	24.7	25.4	9.2
1150061/32-**-XX	1	32	0.21	1.35	0.24	2.10	18.5	19.1	12.2
1150061.5/30-**-XX	1.5	30	0.26	1.70	0.24	2.40	12.7	13	17.3
1150062/28-**-XX	2	28	0.31	2.00	0.28	2.80	9.42	9.69	23.4
1150062/30-**-XX	2	30	0.31	2.00	0.28	2.80	9.42	9.69	22.4
1150062.5/50-**-XX	2.5	50	0.26	2.20	0.28	3.00	7.6	7.82	27.9
1150063/44-**-XX	3	44	0.31	2.40	0.32	3.40	6.15	6.36	35.6
1150064/56-**-XX	4	56	0.31	2.75	0.32	3.70	4.71	4.85	44.5
1150065/65-**-XX	5	65	0.32	3.25	0.32	4.20	3.94	4.02	58.8
1150066/84-**-XX	6	84	0.31	3.30	0.32	4.30	3.14	3.23	65.3
1150068/100-**-XX	8	100	0.33	4.30	0.32	5.00	2.38	2.52	82.7
11500610/80-**-XX	10	80	0.41	4.50	0.48	6.00	1.82	1.85	107.8
11500616/126-**-XX	16	126	0.41	5.50	0.52	7.20	1.16	1.18	164.7
11500625/196-**-XX	25	196	0.41	7.00	0.52	8.70	0.743	0.757	255.9
11500635/276-**-XX	35	276	0.41	8.30	0.64	10.40	0.527	0.538	360.5

Table Notes

† Part No. code: XX = colour code — BK Black, WH White, RD Red, GN Green, BN Brown, BL Blue, OR Orange, YW Yellow, VT Violet, GY Grey, PK Pink, TN Tan, CL Clear.

‡ Replace ** with the conductor code: AS for bare copper or TS for tinned copper.

Please confirm application-specific requirements with CASMO before ordering. Specifications are subject to change; please ensure you are using the latest revision.

© CASMO CABLE LLC. All rights reserved.