FLUY

105°C, 25/60V



Construction
Conductor: Flexible Bare Copper or Flexible Tinned Copper
Insulation: Extruded · PVC

Thermal Characteristics
Operating Temperature: 105°C

Electrical Characteristics
Operating Voltage: 25/60V

Application
Automotive Low-Voltage Circuits: Ultra-thin-wall primary wiring for low-voltage automotive circuits.

General Characteristics
Ultra-Thin Wall: Ultra-thin insulation keeps the finished cable small for dense, lightweight harnesses.
Flexible Routing: Flexible stranded construction for easy routing in tight harness runs.

Standards & Approvals
ISO 19642-3: Low-voltage single-core cables for automobiles.
ISO 6722-1: Test methods for single-core automotive cables.

CASMO Part No.	Conductor				Min. Ins. Thickness (mm)	Max. Overall O.D. (mm)	Max. DCR @20°C (Ω/km)		Nom. Cable Weight (kg/km)
	Conductor Size (mm²)	No. Of Strands	Max. Strand Dia. (mm)	Max. Conductor Dia. (mm)			BC	TPC	
1150030.22/7-**-XX	0.22	7	0.21	0.70	0.16	1.05	84.8	86.5	3.2
1150030.35/7-**-XX	0.35	7	0.27	0.80	0.16	1.20	54.4	55.5	4.3
1150030.5/19-**-XX	0.5	19	0.20	1.00	0.16	1.40	37.1	38.2	6.0
1150030.75/19-**-XX	0.75	19	0.24	1.20	0.16	1.60	24.7	25.4	8.6
1150031/19-**-XX	1	19	0.27	1.35	0.16	1.75	18.5	19.1	10.9
1150031.25/19-**-XX	1.25	19	0.29	1.45	0.30	2.00	14.9	15.9	13.0
1150031.5/19-**-XX	1.5	19	0.33	1.70	0.16	2.10	12.7	13	15.9
1150032.5/19-**-XX	2.5	19	0.41	2.20	0.20	2.70	7.6	7.82	26.6

Table Notes

† Part No. code: XX = colour code — BK Black, WH White, RD Red, GN Green, BN Brown, BL Blue, OR Orange, YW Yellow, VT Violet, GY Grey, PK Pink, TN Tan, CL Clear.

‡ Replace ** with the conductor code: AS for bare copper or TS for tinned copper.

Please confirm application-specific requirements with CASMO before ordering. Specifications are subject to change; please ensure you are using the latest revision.

© CASMO CABLE LLC. All rights reserved.