FLYKW

105°C, 25/60V



Construction
Conductor: Flexible Bare Copper or Flexible Tinned Copper
Insulation: Extruded · PVC

Thermal Characteristics
Operating Temperature: 105°C

Electrical Characteristics
Operating Voltage: 25/60V

Application
Automotive Low-Voltage Circuits: Heat-resistant primary wiring for low-voltage automotive circuits.

General Characteristics
Fluid Resistance: Resists gasoline, diesel and engine oil in vehicle service.
Cold Flexibility: Stays flexible and crack-free in cold conditions.

Standards & Approvals
ISO 19642-3: Low-voltage single-core cables for automobiles.
ISO 6722-1: Test methods for single-core automotive cables.

CASMO Part No.	Conductor				Min. Ins. Thickness (mm)	Max. Overall O.D. (mm)	Max. DCR @20°C (Ω/km)		Nom. Cable Weight (kg/km)
	Conductor Size (mm²)	No. Of Strands	Max. Strand Dia. (mm)	Max. Conductor Dia. (mm)			BC	TPC	
1150090.5/16-**-XX	0.5	16	0.21	1.10	0.48	2.30	37.1	38.2	9.0
1150090.75/24-**-XX	0.75	24	0.21	1.30	0.48	2.50	24.7	25.4	11.9
1150091/32-**-XX	1	32	0.21	1.50	0.48	2.70	18.5	19.1	14.5
1150091.5/30-**-XX	1.5	30	0.26	1.80	0.48	3.00	12.7	13	19.7
1150092/28-**-XX	2	28	0.31	2.00	0.48	3.30	9.42	9.69	25.6
1150092.5/50-**-XX	2.5	50	0.26	2.20	0.56	3.60	7.6	7.82	31.8
1150093/44-**-XX	3	44	0.31	2.40	0.56	4.10	6.15	6.36	39.0
1150094/56-**-XX	4	56	0.31	2.80	0.64	4.40	4.71	4.85	50.7
1150095/65-**-XX	5	65	0.32	3.10	0.64	4.90	3.94	4.02	60.6
1150096/84-**-XX	6	84	0.31	3.40	0.64	5.00	3.14	3.23	70.4
11500910/80-**-XX	10	80	0.41	4.50	0.80	6.50	1.82	1.85	120.2
11500910/325-**-XX	10	325	0.21	4.50	0.80	6.50	1.82	1.85	122.7
11500916/126-**-XX	16	126	0.41	5.80	0.80	8.30	1.16	1.18	188.0
11500925/196-**-XX	25	196	0.41	7.20	1.04	10.40	0.743	0.757	294.1
11500925/790-**-XX	25	790	0.21	7.80	1.04	10.40	0.743	0.757	290.8
11500935/276-**-XX	35	276	0.41	8.50	1.04	11.60	0.527	0.538	399.0
11500935/1070-**-XX	35	1070	0.21	9.00	1.04	11.60	0.527	0.538	408.1
11500950/396-**-XX	50	396	0.41	10.50	1.20	13.50	0.368	0.375	553.5
11500970/360-**-XX	70	360	0.51	12.50	1.20	15.50	0.259	0.264	811.3
11500995/475-**-XX	95	475	0.51	14.80	1.28	18.00	0.196	0.2	1075.2

Please confirm application-specific requirements with CASMO before ordering. Specifications are subject to change; please ensure you are using the latest revision.

© CASMO CABLE LLC. All rights reserved.

FLYKW

105°C, 25/60V



Table Notes

† Part No. code: XX = colour code — BK Black, WH White, RD Red, GN Green, BN Brown, BL Blue, OR Orange, YW Yellow, VT Violet, GY Grey, PK Pink, TN Tan, CL Clear.

‡ Replace ** with the conductor code: AS for bare copper or TS for tinned copper.

Please confirm application-specific requirements with CASMO before ordering. Specifications are subject to change; please ensure you are using the latest revision.

© CASMO CABLE LLC. All rights reserved.