casmocable
CABLES FOR EXTREMES

NEMA HP 4 TYPE K

-65°C to +200°C, 600V



Construction
Conductor: Silver Plated Copper or Nickel Plated Copper or Tin Coated Copper
Insulation: Extruded · FEP

Thermal Characteristics
Operating Temperature: -65°C to +200°C
Conductor Plating Temperature Rating:
Silver/Nickel-Plated Copper: -65°C to +200°C · Tin-Coated Copper: -65°C to +150°C

Electrical Characteristics
Operating Voltage: 600V

Application
High-reliability equipment wiring: Internal wiring for electrical and electronic equipment, aviation and aircraft systems per ANSI/NEMA HP 4-2021 Type K (ex. MIL-W-16878/11).

General Characteristics
Zero Solder Melt-Back: High-purity fluoropolymer insulation resists soldering iron heat without shrink-back or melting.
Fluid & Chemical Inertness: Resists fuels, lubricants, hydraulic fluids, oils, acids, alkalis, and industrial solvents.
Low Dielectric Loss: Stable low dielectric constant and dissipation factor support clean high-frequency and signal transmission.

Standards & Approvals
ANSI/NEMA HP 4: FEP-insulated high-temperature hook-up wire, TYPE K (medium wall, 600 V).
MIL-W-16878/11 (Superseded): Former military specification superseded by NEMA HP 4 TYPE K.

RoHS COMPLIANT REACH COMPLIANT

CASMO Part No.	Conductor			Cable		Max. DCR @20°C (Ω/km)	Nom. Cable Weight (kg/km)
	Conductor Size (AWG)	No. Of Strands	Strand Size (AWG)	Min. Overall O.D. (mm)	Max. Overall O.D. (mm)		
HP4K-XBCB*	28	7	36	0.787	0.991	208.66	2.98
HP4K-XBDA*	26	1	26	0.813	1.016	137.47	2.98
HP4K-XBDB*	26	7	34	0.889	1.092	130.25	2.98
HP4K-XBDE*	26	19	38	0.889	1.118	122.38	2.98
HP4K-XBEA*	24	1	24	0.914	1.118	85.96	4.46
HP4K-XBEB*	24	7	32	1.016	1.219	80.38	4.46
HP4K-XBEE*	24	19	36	1.016	1.219	77.43	4.46
HP4K-XBFA*	22	1	22	1.041	1.27	54.13	5.95
HP4K-XBFB*	22	7	30	1.168	1.372	51.18	5.95
HP4K-XBFE*	22	19	34	1.168	1.372	48.56	5.95
HP4K-XBGA*	20	1	20	1.219	1.422	33.79	7.44
HP4K-XBGB*	20	7	28	1.372	1.575	32.19	7.44
HP4K-XBGE*	20	19	32	1.372	1.575	29.86	7.44
HP4K-XBHB*	18	7	26	1.626	1.88	20.21	11.9
HP4K-XBHE*	18	19	30	1.626	1.88	19	11.9
HP4K-XBJE*	16	19	29	1.854	2.21	14.9	14.88
HP4K-XBKE*	14	19	27	2.235	2.591	9.42	22.32

Please confirm application-specific requirements with CASMO before ordering. Specifications are subject to change; please ensure you are using the latest revision.

© CASMO CABLE LLC. All rights reserved.

NEMA HP 4 TYPE K

-65°C to +200°C, 600V



CASMO Part No.	Conductor			Cable		Max. DCR @20°C (Ω/km)	Nom. Cable Weight (kg/km)
	Conductor Size (AWG)	No. Of Strands	Strand Size (AWG)	Min. Overall O.D. (mm)	Max. Overall O.D. (mm)		
HP4K-XBLE*	12	19	25	2.718	3.073	5.94	34.23
HP4K-XBMG*	10	37	26	3.226	3.581	3.9	52.08

Table Notes

* Part numbers shown represent extruded FEP (X) insulation and silver-plated copper conductor (B). Replace "*" with color digit 0–9 per the Color Code Chart below.

1. Conductor diameter and overall O.D. limits per ANSI/NEMA HP 4; Max. DCR is stated for silver-plated copper (SPC) at 20°C; cable weight is nominal reference value.

COLOR CODE CHART					
Cond. #	Color	Cond. #	Color	Cond. #	Color
0	Black	4	Yellow	8	Gray
1	Brown	5	Green	9	White
2	Red	6	Blue		
3	Orange	7	Violet		

Please confirm application-specific requirements with CASMO before ordering. Specifications are subject to change; please ensure you are using the latest revision.

© CASMO CABLE LLC. All rights reserved.