RTD-AAP

-65°C to +260°C



Construction
Conductor: Nickel Plated Copper · Stranded
Core Insulation: Extruded · PFA
Cabling: Laid Up · 3-core concentric twist
Core Identification: 3-wire IEC 60751 color code (2 Red + 1 White)
Jacket: Extruded · PFA
Braid: Stainless steel wire overbraid (304 SS)

Thermal Characteristics
Operating Temperature: -65°C to +260°C

Electrical Characteristics
Signal Circuit Duty: Low-voltage RTD excitation and bridge measurement signal circuits only (not rated for mains power distribution); extruded core insulation is factory dielectric-verified at 1000 V AC for 1 min.

Application
PT100 and RTD Resistance Thermometry: For three-wire resistance thermometer lead connections between RTD sensors, transmitters and temperature controllers.
High-Temperature Ovens, Kilns and Heat Treatment: For high-temperature Pt100 / RTD resistance sensor lead wiring on industrial ovens, autoclaves, heat-treating equipment and thermal processing lines.
Process & Plant RTD Instrumentation: For Pt100 / Pt1000 resistance sensor lead circuits across power-generation, chemical, petrochemical and metallurgical facilities.

General Characteristics
Low-Resistance Lead Compensation: Matched three-conductor copper construction minimizes lead-wire resistance imbalance in bridge-connected RTD circuits.
Stainless Steel Overbraid Protection: Woven 304 stainless steel wire armor protects the cable against mechanical abrasion, cut-through and crush loads.
High-Temperature Thermal Stability: Heat-resistant insulation and jacketing resist thermal aging, embrittlement and cut-through in elevated-temperature zones.
Chemical Resistance: Resistant to chemical exposure, helping protect the cable covering against deterioration in chemically demanding environments.

Standards & Approvals
IEC 60751: 3-wire platinum resistance thermometer (PT100 / PT1000) lead-cable configuration and color identification.
ASTM E1137: Industrial platinum resistance thermometry wiring compatibility.
ASTM B355 Class 2: 2% nickel-coated soft copper conductors for continuous 260°C PFA RTD instrumentation service.

Product illustrations are representative only and nominal values are for reference (Cal. Com. Code § 2313); binding acceptance is governed by CASMO's order acknowledgment, signed drawing, and applicable agency scope. Standards cited without a corresponding agency mark indicate design/test reference only. Specifications are subject to change; confirm latest revision and Terms of Sale at casmocable.com/terms.

© CASMO CABLE LLC. All rights reserved. UL®, cUL®, and UL certification marks are trademarks of UL LLC; CSA® is a trademark of CSA Group; TÜV Rheinland® is a trademark of TÜV Rheinland AG.

casmocable
CABLES FOR EXTREMES

RTD-AAP

-65°C to +260°C



CASMO Part No.	Total Cores	Conductor				Insulation		Nom. Jkt. Thickness (mm)	Nom. Shield Thickness (mm)	Cable	
		Conductor Size (AWG)	No. Of Strands	Nom. Strand Dia. (mm)	Nom. Conductor Dia. (mm)	Nom. Ins. Thickness (mm)	Nom. Core O.D. (mm)			Nom. O.D. (mm)	O.D. Tolerance ± (mm)
710393C26-NS-XX	3	26	7	0.16	0.48	0.2	0.9	0.5	0.2	3.3	0.2
710393C24-NS-XX	3	24	7	0.2	0.6	0.2	1.0	0.5	0.2	3.6	0.2
710393C22-NS-XX	3	22	7	0.254	0.76	0.2	1.2	0.5	0.2	4.0	0.2
710393C20-NS-XX	3	20	7	0.32	0.96	0.2	1.4	0.5	0.2	4.4	0.2
710393C18-NS-XX	3	18	7	0.39	1.17	0.25	1.7	0.5	0.2	5.1	0.3
710393C16-NS-XX	3	16	19	0.3	1.5	0.25	2.0	0.5	0.2	5.7	0.3
710393C14-NS-XX	3	14	19	0.37	1.85	0.25	2.4	0.5	0.2	6.6	0.3

Table Notes

* "-NS-" = stranded 2% nickel-plated copper conductor (standard for 260°C PFA RTD cable). Standard 3-core IEC 60751 configuration (2 Red + 1 White); 2-core (2C) and 4-core (4C) constructions available upon request.

† "-XX" = PFA inner jacket color code under natural 304 stainless steel wire overbraid: RD Red (standard), WH White, BK Black, or GY Grey (3-core identification per Color Code Chart below).

COLOR CODE CHART					
Cond. #	Color	Cond. #	Color	Cond. #	Color
1	Red (Lead A)	2	Red (Lead A')	3	White (Sense B)

Product illustrations are representative only and nominal values are for reference (Cal. Com. Code § 2313); binding acceptance is governed by CASMO's order acknowledgment, signed drawing, and applicable agency scope. Standards cited without a corresponding agency mark indicate design/test reference only. Specifications are subject to change; confirm latest revision and Terms of Sale at casmocable.com/terms.

© CASMO CABLE LLC. All rights reserved. UL®, cUL®, and UL certification marks are trademarks of UL LLC; CSA® is a trademark of CSA Group; TÜV Rheinland® is a trademark of TÜV Rheinland AG.