RTD-GG

0°C to +480°C



Construction
Conductor: Nickel-Coated Copper (27%) or Pure Nickel · Stranded
Core Insulation: Braided · Fiberglass
Cabling: Laid Up · 3-core concentric twist
Core Identification: 3-wire IEC 60751 high-temperature tracer code (2 White w/ Red tracer + 1 Solid White)
Jacket: Braided · Fiberglass

Thermal Characteristics
Operating Temperature: 0°C to +480°C
Saturant & Tracer Volatilization: High-temperature silicone resin saturant and organic dye tracers volatilize above +204°C while braided fiberglass insulation maintains continuous electrical separation up to +480°C; retain polarity tags at cold terminations.

Electrical Characteristics
Signal Circuit Duty: Dry-location low-voltage RTD measurement signal circuits only; porous braided fiberglass insulation is not voltage-rated for mains power circuits.

Application
PT100 and RTD Resistance Thermometry: For three-wire resistance thermometer lead connections between RTD sensors, transmitters and temperature controllers.
High-Temperature Ovens, Kilns and Heat Treatment: For high-temperature Pt100 / RTD resistance sensor lead wiring on industrial ovens, autoclaves, heat-treating equipment and thermal processing lines.
Process & Plant RTD Instrumentation: For Pt100 / Pt1000 resistance sensor lead circuits across power-generation, chemical, petrochemical and metallurgical facilities.

General Characteristics
Low-Resistance Lead Compensation: Matched three-conductor copper construction minimizes lead-wire resistance imbalance in bridge-connected RTD circuits.
High-Temperature Thermal Stability: Heat-resistant insulation and jacketing resist thermal aging, embrittlement and cut-through in elevated-temperature zones.
Abrasion Resistance: Resistant to abrasion, helping protect the cable surface against wear caused by rubbing and handling.
Flexibility: Flexible construction facilitates routing, bending and installation where space is limited.

Standards & Approvals
IEC 60751: 3-wire platinum resistance thermometer (PT100 / PT1000) lead-cable configuration and color identification.
ASTM E1137: Industrial platinum resistance thermometry wiring compatibility.
ASTM B355 Class 27 / ASTM B160: 27% nickel-coated copper conductors (standard for 480°C service) or optional Nickel 200 pure nickel conductors.

Product illustrations are representative only and nominal values are for reference (Cal. Com. Code § 2313); binding acceptance is governed by CASMO's order acknowledgment, signed drawing, and applicable agency scope. Standards cited without a corresponding agency mark indicate design/test reference only. Specifications are subject to change; confirm latest revision and Terms of Sale at casmocable.com/terms.

© CASMO CABLE LLC. All rights reserved. UL®, cUL®, and UL certification marks are trademarks of UL LLC; CSA® is a trademark of CSA Group; TÜV Rheinland® is a trademark of TÜV Rheinland AG.

casmocable
CABLES FOR EXTREMES

RTD-GG

0°C to +480°C



CASMO Part No.	Total Cores	Conductor				Insulation		Cable		
		Conductor Size (AWG)	No. Of Strands	Nom. Strand Dia. (mm)	Nom. Conductor Dia. (mm)	Nom. Ins. Thickness (mm)	Nom. Core O.D. (mm)	Nom. Jkt. Thickness (mm)	Nom. O.D. (mm)	O.D. Tolerance ± (mm)
710413C26-NC27-XX	3	26	7	0.16	0.48	0.2	0.9	0.2	2.3	0.2
710413C24-NC27-XX	3	24	7	0.2	0.6	0.2	1.0	0.2	2.6	0.2
710413C22-NC27-XX	3	22	7	0.254	0.76	0.2	1.2	0.2	3.0	0.2
710413C20-NC27-XX	3	20	7	0.32	0.96	0.2	1.4	0.2	3.4	0.2
710413C18-NC27-XX	3	18	7	0.39	1.17	0.2	1.6	0.2	3.8	0.2
710413C16-NC27-XX	3	16	19	0.3	1.5	0.2	1.9	0.2	4.5	0.2
710413C14-NC27-XX	3	14	19	0.37	1.85	0.2	2.3	0.2	5.4	0.2

Table Notes

* "-NC27-" = stranded 27% nickel-coated copper conductor (standard for 480°C fiberglass RTD cable). "-N-" = pure nickel conductor (optional). Standard 3-core IEC 60751 configuration (2 White w/ Red tracer + 1 Solid White); 2-core (2C) and 4-core (4C) constructions available upon request.

† "-XX" = outer braid finish code (WH White fiberglass braid with Red tracer standard; custom tracer colors available upon request).

COLOR CODE CHART					
Cond. #	Color	Cond. #	Color	Cond. #	Color
1	White w/ Red tracer (Lead A)	2	White w/ Red tracer (Lead A')	3	Solid White (Sense B)

Product illustrations are representative only and nominal values are for reference (Cal. Com. Code § 2313); binding acceptance is governed by CASMO's order acknowledgment, signed drawing, and applicable agency scope. Standards cited without a corresponding agency mark indicate design/test reference only. Specifications are subject to change; confirm latest revision and Terms of Sale at casmocable.com/terms.

© CASMO CABLE LLC. All rights reserved. UL®, cUL®, and UL certification marks are trademarks of UL LLC; CSA® is a trademark of CSA Group; TÜV Rheinland® is a trademark of TÜV Rheinland AG.