SGT

80°C, 25/60V



Construction
Conductor: Tinned Copper or Bare Copper
Insulation: Extruded · PVC

Thermal Characteristics
Operating Temperature: 80°C
Optional Temperature Class: 100°C (SAE Class 2) available upon request.

Electrical Characteristics
Operating Voltage: 25/60V

Application
Automotive Battery Cable: Battery cable for starter, ground and high-current connections in surface vehicles.

General Characteristics
Fluid Resistance: Resists common vehicle fluids in under-hood service.
Cold Flexibility: Stays flexible and crack-free in cold conditions.

Standards & Approvals
SAE J1127: Low Voltage Battery Cable: covers battery cable for starter, ground and other high-current connections at nominal system voltages of 60 V DC / 25 V AC or less; SGT is the general-purpose type with thermoplastic insulation.

CASMO Part No.	Conductor			Insulation		Max. Overall O.D. (mm)	Nom. Cable Weight (kg/km)
	Conductor Size (AWG)	No. Of Strands	Nom. Strand Dia. (mm)	Nom. Insulation Thickness (mm)	Min. Ins. Thickness (mm)		
1140096/266-**-XX	6	266	0.254	1.52	1.06	8.6	167
1140094/420-**-XX	4	420	0.254	1.65	1.16	10.5	256
1140092/627-**-XX	2	627	0.254	1.65	1.16	12	358
1140091/837-**-XX	1	837	0.254	1.65	1.16	13	467
1140091_0/969-**-XX	1/0	969	0.254	1.65	1.16	14.5	531
1140092_0/1330-**-XX	2/0	1330	0.254	1.65	1.16	16	715
1140093_0/1547-**-XX	3/0	1547	0.254	1.98	1.39	18.5	843
1140094_0/2146-**-XX	4/0	2146	0.254	1.98	1.39	20	1145
114009250MCM/2496-**-XX	250MCM	2496	0.254	1.98	1.39	22	1296

Table Notes

† Replace XX with the color code when ordering (e.g. BK, WH, RD, GN, BN, BL, OR, YW, VT, GY, PK, TN, CL).

‡ Replace ** with the conductor code: AS for bare copper or TS for tinned copper.

Please confirm application-specific requirements with CASMO before ordering. Specifications are subject to change; please ensure you are using the latest revision.

© CASMO CABLE LLC. All rights reserved.