STT

80°C, 25/60V



Construction
Conductor: Tinned Copper or Bare Copper
Insulation: Extruded · PVC

Thermal Characteristics
Operating Temperature: 80°C
Optional Temperature Class: 100°C (SAE Class 2) available upon request.

Electrical Characteristics
Operating Voltage: 25/60V

Application
Automotive Battery Cable: Thin-wall battery cable for starter, ground and high-current connections in surface vehicles.

General Characteristics
Thin-Wall Construction: Thin thermoplastic insulation reduces cable profile and weight in tight routing paths.
Fluid Resistance: Resists common automotive fluids, battery acid and oils in under-hood service.

Standards & Approvals
SAE J1127: Low Voltage Battery Cable: covers battery cable for starter, ground and other high-current connections at nominal system voltages of 60 V DC / 25 V AC or less; STT is the thin-wall type with thermoplastic (PVC) insulation.

CASMO Part No.	Conductor			Insulation		Max. Overall O.D. (mm)	Nom. Cable Weight (kg/km)
	Conductor Size (AWG)	No. Of Strands	Nom. Strand Dia. (mm)	Nom. Insulation Thickness (mm)	Min. Ins. Thickness (mm)		
1140126/266-**-XX	6	266	0.254	1.09	0.76	7.8	152
1140124/420-**-XX	4	420	0.254	1.12	0.78	9.5	233
1140122/627-**-XX	2	627	0.254	1.12	0.78	11	333
1140121/837-**-XX	1	837	0.254	1.12	0.78	12	438
1140121_0/969-**-XX	1/0	969	0.254	1.12	0.78	13	501
1140122_0/1330-**-XX	2/0	1330	0.254	1.12	0.78	14.5	679
1140123_0/1547-**-XX	3/0	1547	0.254	1.12	0.78	17	781
1140124_0/2146-**-XX	4/0	2146	0.254	1.12	0.78	18.5	1071

Table Notes

† Replace XX with the color code when ordering (e.g. BK, WH, RD, GN, BN, BL, OR, YW, VT, GY, PK, TN, CL).

‡ Replace ** with the conductor code: AS for bare copper or TS for tinned copper.

Please confirm application-specific requirements with CASMO before ordering. Specifications are subject to change; please ensure you are using the latest revision.

© CASMO CABLE LLC. All rights reserved.