TC-VV

-20°C to +105°C



Construction
Conductor: Thermocouple Alloy (Type K / J / T / E / N) or Extension / Compensating Alloy (Type KX / JX / TX / EX / NX / RX / SX) · Stranded
Core Insulation: Extruded · PVC
Cabling: Parallel · Duplex parallel flat core pair
Core Identification: Color-coded per IEC 60584-3 (Type K/KX: +Green / -White) or ASTM E230 on request
Jacket: Extruded · PVC

Thermal Characteristics
Operating Temperature: -20°C to +105°C

Electrical Characteristics
Signal Circuit Duty: Low-voltage thermoelectric millivolt EMF measurement and extension signal circuits only (not rated for mains power distribution).

Application
Process Temperature Sensing and Pyrometry: For connecting thermocouple probes and cold-junction transmitters across chemical, petrochemical, power-generation and metallurgical plants.
Control Cabinets: For wiring within control cabinets, control panels and electrical assemblies.
Sensors and Instrumentation: For connections between sensors, measuring instruments and associated control equipment.

General Characteristics
Calibrated EMF Accuracy: Matched thermoelectric conductor pairs maintain stable electromotive force characteristics across the rated temperature span.
Moisture Resistance: Resistant to moisture and humidity, helping maintain the integrity of the cable covering in damp environments.
Oil Resistance: Resistant to oil exposure, helping maintain the integrity of the cable covering in oily environments.
Flexibility: Flexible construction facilitates routing, bending and installation where space is limited.

Standards & Approvals
IEC 60584-1 / IEC 60584-3: EMF tolerances (Class 1 / Class 2) and international thermocouple & extension cable color identification.
ASTM E230 / E230M: Standard and special limits of error and North American thermocouple & extension color coding.

Product illustrations are representative only and nominal values are for reference (Cal. Com. Code § 2313); binding acceptance is governed by CASMO's order acknowledgment, signed drawing, and applicable agency scope. Standards cited without a corresponding agency mark indicate design/test reference only. Specifications are subject to change; confirm latest revision and Terms of Sale at casmocable.com/terms.

© CASMO CABLE LLC. All rights reserved. UL®, cUL®, and UL certification marks are trademarks of UL LLC; CSA® is a trademark of CSA Group; TÜV Rheinland® is a trademark of TÜV Rheinland AG.

casmocable
CABLES FOR EXTREMES

TC-VV

-20°C to +105°C



CASMO Part No.	Total Cores	Conductor				Insulation		Nom. Jkt. Thickness (mm)	Nom. Overall Width (mm)	Overall Width Tolerance ± (mm)	Nom. Overall Thickness (mm)	Overall Thickness Tolerance ± (mm)
		Conductor Size (AWG)	No. Of Strands	Nom. Strand Dia. (mm)	Nom. Conductor Dia. (mm)	Nom. Ins. Thickness (mm)	Nom. Core O.D. (mm)					
710012C26-KX-XX	2	26	7	0.16	0.48	0.3	1.1	0.5	3.2	0.2	2.1	0.2
710012C24-KX-XX	2	24	7	0.2	0.6	0.3	1.2	0.5	3.4	0.2	2.2	0.2
710012C22-KX-XX	2	22	7	0.254	0.76	0.3	1.4	0.5	3.8	0.2	2.4	0.2
710012C20-KX-XX	2	20	7	0.32	0.96	0.3	1.6	0.5	4.2	0.2	2.6	0.2
710012C18-KX-XX	2	18	7	0.39	1.17	0.4	2.0	0.6	5.2	0.2	3.2	0.2
710012C16-KX-XX	2	16	19	0.3	1.5	0.4	2.3	0.6	5.8	0.2	3.5	0.2
710012C14-KX-XX	2	14	19	0.37	1.85	0.4	2.7	0.6	6.6	0.2	3.9	0.2

Table Notes

* "-KX-" = Type KX extension-grade alloy pair (NiCr / NiAl, standard; EMF calibrated up to +200°C). Substitute "-JX-", "-EX-", "-NX-", "-RX-", "-SX-" (EMF calibrated ≤ +200°C), "-TX-" (EMF calibrated ≤ +100°C), or thermocouple-grade "-K-", "-J-", "-T-", "-E-", "-N-" for sensing-junction service (Type T wire-gauge limit: +200°C for 26–20 AWG).

† "-XX" = color-code suffix: IEC 60584-3 color code supplied as standard (e.g., GN for Type K/KX); ASTM E230 color code available upon request (see Color Code Chart below).

COLOR CODE CHART					
Cond. #	Color	Cond. #	Color	Cond. #	Color
IEC K / KX	+Green / -White (Jkt: Green)	IEC N / NX	+Pink / -White (Jkt: Pink)	ASTM T / TX	+Blue / -Red (TC: Brown / Ext: Blue; TX ≤100°C)
IEC J / JX	+Black / -White (Jkt: Black)	IEC RCA / SCA	+Orange / -White (Jkt: Orange; ≤100°C)	ASTM E / EX	+Purple / -Red (TC: Brown / Ext: Purple)
IEC T / TX	+Brown / -White (Jkt: Brown; TX ≤100°C)	ASTM K / KX	+Yellow / -Red (TC: Brown / Ext: Yellow)	ASTM N / NX	+Orange / -Red (TC: Brown / Ext: Orange)
IEC E / EX	+Violet / -White (Jkt: Violet)	ASTM J / JX	+White / -Red (TC: Brown / Ext: Black)	ASTM RX / SX	+Black / -Red (Ext: Green; ≤200°C)

Product illustrations are representative only and nominal values are for reference (Cal. Com. Code § 2313); binding acceptance is governed by CASMO's order acknowledgment, signed drawing, and applicable agency scope. Standards cited without a corresponding agency mark indicate design/test reference only. Specifications are subject to change; confirm latest revision and Terms of Sale at casmocable.com/terms.

© CASMO CABLE LLC. All rights reserved. UL®, cUL®, and UL certification marks are trademarks of UL LLC; CSA® is a trademark of CSA Group; TÜV Rheinland® is a trademark of TÜV Rheinland AG.