

**Electrical Wire Ordering Info:**

**Example : HP**



NEMA Type

**Construction**

**X** — Extruded

**W** — Wrapped (HP3 only)

Conductor material	
B	Silver plated copper
C	Nickel plated copper
D	Silver plated high-strength alloy
E	Nickel plated high-strength alloy
F	Silver plated copper clad steel
G	Nickel plated copper clad steel
H	Tin plated copper (HP4 only)

AWG Size	
B	30
C	28
D	26
E	24
F	22
G	20
H	18
J	16
K	14
L	12
M	10
N	8
P	6
R	4
S	2
T	1
U	1/0
W	2/0
Y	3/0
Z	4/0

Stranding	
A	1
B	7
E	19
G	37
L	133
P	665
R	817
S	1045
T	1330
V	1665
W	2109

Color Code	
0	Black
1	Brown
2	Red
3	Orange
4	Yellow
5	Green
6	Blue
7	Violet
8	Gray

**COPYRIGHT**

This document is protected under copyright law and is the property of Casmo Cable. Data contained herein is confidential to Casmo Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmo Cable or any affiliates without the prior written authorization of Casmo Cable.

**CAUTION**

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmo Cable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmo Cable is not responsible for any claim traceable to such error.



## CASFLON™ NEMA

### HP3 Type E, EE, ET

-65°C to +200°C or 260°C, 250-600V



#### Construction

**Type:** electrical wire

**Core:** silver-plated copper or nickel plated copper

**Insulation:** extruded PTFE

#### Production

**Range width:** AWG 28 to 6

**Options:** contact us for more options

#### Application

**Aviation:** Electrical lightweight cables used in electronic equipment for aircraft, missile systems or aeronautical test benches

#### General characteristics

**Weather conditions:** excellent resistance to UV

**Chemical behaviors:** excellent resistance to aggressive chemical environments

**Humidity:** excellent resistance to humidity

**Mechanical behaviors:** excellent mechanical strength

#### Thermal characteristics

**Operating temperature:** SPC: -65°C to +200°C

NPC: -65°C to +260°C

#### Electrical characteristics

**Operating Voltage:** Type E: 600V

Type EE: 1000V

Type ET: 250V

#### Approvals – Standards

**NEMA standard:** NEMA HP3 Type E, EE, Et ex. MIL-W-16878/ 4 / 5 / 6 / 23 / 25 / 27

**UL :** XE 18 awg & smaller dual rated to UL1213

XEE 18 awg & smaller dual rated to UL1180

### Type E, ex. MIL-W-16878/4 600V

CASMO.P.N	AWG/Stranding	Insulation Thickness		O.D.		Weight	
		(inch)	(mm)	(inch)	(mm)	(lbs/mft)	(kg/km)
HP3E-XBCB	28 7/36	0.01	0.254	0.035	0.89	2	2.98
HP3E-XBDA	26 1/26	0.01	0.254	0.036	0.91	2	2.98
HP3E-XBDB	26 7/34	0.01	0.254	0.039	0.99	2	2.98
HP3E-XBDE	26 19/38	0.01	0.254	0.039	0.99	2	2.98
HP3H-XBEA	24 1/24	0.01	0.254	0.04	1.02	3	4.46
HP3E-XBEB	24 7/32	0.01	0.254	0.044	1.12	3	4.46
HP3E-XBEE	24 19/36	0.01	0.254	0.045	1.14	3	4.46
HP3E-XBFA	22 1/22	0.01	0.254	0.045	1.14	4	5.95
HP3E-XBFB	22 7/30	0.01	0.254	0.05	1.27	4	5.95
HP3E-XBFE	22 19/34	0.01	0.254	0.051	1.30	4	5.95
HP3E-XBGA	20 1/20	0.01	0.254	0.052	1.32	5	7.44
HP3E-XBGB	20 7/28	0.01	0.254	0.058	1.47	5	7.44
HP3E-XBGE	20 19/32	0.01	0.254	0.058	1.47	6	8.93
HP3E-XBHB	18 7/26	0.01	0.254	0.069	1.75	8	11.90
HP3E-XBHE	18 19/30	0.01	0.254	0.069	1.75	8	11.90
HP3E-XBJE	16 19/29	0.013	0.330	0.08	2.03	10	14.88
HP3E-XBKE	14 19/27	0.013	0.330	0.095	2.41	15	22.32
HP3E-XBLE	12 19/25	0.015	0.381	0.114	2.90	23	34.23
HP3E-XBMG	10 37/26	0.013	0.330	0.134	3.40	35	52.08

#### COPYRIGHT

This document is protected under copyright law and is the property of Casmo Cable. Data contained herein is confidential to Casmo Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmo Cable or any affiliates without the prior written authorization of Casmo Cable

#### CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmo Cable for dimensional verification, information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmo Cable is not responsible for any claim traceable to such error.



## CASFLON™ NEMA

### HP3 Type E, EE, ET

-65°C to +200°C or 260°C, 250-600V



### Type EE, ex. MIL-W-16878/5 1000V

CASMO .P.N	AWG/Stranding	Insulation Thickness		O.D.		Weight	
		(inch)	(mm)	(inch)	(mm)	(lbs/mft)	(kg/km)
HP3EE-XBCB	28 7/36	0.015	0.381	0.045	1.143	2	3
HP3EE-XBDA	26 1/26	0.015	0.381	0.046	1.1684	2	3
HP3EE-XBDB	26 7/34	0.015	0.381	0.049	1.2446	2	3
HP3EE-XBDE	26 19/38	0.015	0.381	0.049	1.2446	2	3
HP3EE-XBEA	24 1/24	0.015	0.381	0.05	1.27	3	4
HP3EE-XBEB	24 7/32	0.015	0.381	0.054	1.3716	3	4
HP3EE-XBEE	24 19/36	0.015	0.381	0.055	1.397	3	4
HP3EE-XBFA	22 1/22	0.015	0.381	0.055	1.397	4	6
HP3EE-XBFB	22 7/30	0.015	0.381	0.06	1.524	4	6
HP3EE-XBFE	22 19/34	0.015	0.381	0.061	1.5494	5	7
HP3EE-XBGA	20 1/20	0.015	0.381	0.062	1.5748	6	9
HP3EE-XBGB	20 7/28	0.015	0.381	0.068	1.7272	6	9
HP3EE-XBGE	20 19/32	0.015	0.381	0.068	1.7272	7	10
HP3EE-XBHB	18 7/26	0.015	0.381	0.079	2.0066	9	13
HP3EE-XBHE	18 19/30	0.015	0.381	0.079	2.0066	9	13
HP3EE-XBJE	16 19/29	0.018	0.457	0.089	2.2606	11	16
HP3EE-XBKE	14 19/27	0.018	0.457	0.106	2.6924	17	25
HP3EE-XBKE	12 19/25	0.021	0.533	0.125	3.175	24	36
HP3EE-XBMG	10 37/26	0.019	0.483	0.145	3.683	35	52
HP3EE-XBNL	8 133/27	0.024	0.610	0.209	5.3086	68	101
HP3EE-XBPL	6 133/29	0.028	0.711	0.263	6.6802	107	159

**COPYRIGHT**

This document is protected under copyright law and is the property of Casmo Cable. Data contained herein is confidential to Casmo Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmo Cable or any affiliates without the prior written authorization of Casmo Cable.

**CAUTION**

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmo Cable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmo Cable is not responsible for any claim traceable to such error.



**CASFLON™ NEMA**

**HP3 Type E, EE, ET**

**-65°C to +200°C or 260°C, 250-600V**



**Type ET, ex. MIL-W-16878/6 250V**

CASMO .P.N	AWG/Stranding	Insulation Thickness		O.D.		Weight	
		(inch)	(mm)	(inch)	(mm)	(lbs/mft)	(kg/km)
HP3ET-XBCB	28 7/36	0.006	0.152	0.027	0.69	1	1.49
HP3ET-XBDA	26 1/26	0.006	0.152	0.028	0.71	2	2.98
HP3ET-XBDB	26 7/34	0.006	0.152	0.031	0.79	2	2.98
HP3ET-XBDE	26 19/38	0.006	0.152	0.031	0.79	2	2.98
HP3ET-XBEA	24 1/24	0.006	0.152	0.032	0.81	3	4.46
HP3ET-XBEB	24 7/32	0.006	0.152	0.036	0.91	3	4.46
HP3ET-XBEE	24 19/36	0.006	0.152	0.036	0.91	3	4.46
HP3ET-XBFA	22 1/22	0.006	0.152	0.038	0.97	3	4.46
HP3ET-XBFB	22 7/30	0.006	0.152	0.042	1.07	3	4.46
HP3ET-XBFE	22 19/34	0.006	0.152	0.042	1.07	4	5.95
HP3ET-XBGA	20 1/20	0.006	0.152	0.044	1.12	5	7.44
HP3ET-XBGB	20 7/28	0.006	0.152	0.05	1.27	5	7.44
HP3ET-XBGE	20 19/32	0.006	0.152	0.05	1.27	5	7.44

**COPYRIGHT**

This document is protected under copyright law and is the property of Casmo Cable. Data contained herein is confidential to Casmo Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmo Cable or any affiliates without the prior written authorization of Casmo Cable.

**CAUTION**

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmo Cable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmo Cable is not responsible for any claim traceable to such error.

