

## CASLICON™ 200 UL/cUL

**Style 3530**  
-60°C to +150°C/200 °C, 600V



### Construction

**Type:** electrical wire

**Core:** bare, tin-plated, nickel-plated, or silver-plated copper

**Insulation:** silicon rubber

### Production

**Range width:** AWG 26 to 12

**Options:** Please consult us for any special requirements

### Application

**Lighting:** industrial cabling in hot atmospheres

**Industry:** cabling for industrial machines

**Electromechanics:** cabling for rotating machines

**Household appliances:** cabling for household electrical heating appliances

### General characteristics

**Weather conditions:** good resistance to UV

**Operating environment:** good resistance to thermal shock

### Thermal characteristics

**Operating temperature:** -60°C to +150 °C /200 °C

### Electrical characteristics

**Operating Voltage:** 600V

**Test voltage:** 2000 V

### Approvals – Standards

**“Horizontal flame”:** IEC 60754-2 / EN 60754-2

**“FT1 flame rating”:** as per UL approval

**“VW-1 flame test”:** as per UL approval

**UL approval:** as per standard UL 758

Casmco Part No.	Wire gauge	Conductor structure			Conductor Diameter		Wall thickness		Final O.D.		Approx, Wt.	
	(AWG)	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb./kft)	(kg/km)
			(in)	(mm)								
3210301	12	49	0.012	0.3	0.106	2.7	0.031	0.78	0.168	4.26	24.84	36.96
3210302	14	40	0.012	0.3	0.075	1.9	0.031	0.78	0.136	3.46	18.44	27.44
3210303	16	7	0.020	0.5	0.059	1.5	0.031	0.78	0.120	3.06	10.31	15.34
3210304	17	32	0.008	0.2	0.053	1.34	0.031	0.78	0.114	2.9	8.60	12.79
3210305	18	7	0.016	0.4	0.047	1.2	0.031	0.78	0.109	2.76	6.88	24.40
3210306	20	7	0.013	0.32	0.038	0.96	0.031	0.78	0.099	2.52	4.77	16.40
3210307	22	7	0.010	0.26	0.031	0.78	0.031	0.78	0.092	2.34	3.40	14.80
3210308	24	7	0.008	0.2	0.024	0.6	0.031	0.78	0.085	2.16	2.49	13.10
3210309	26	7	0.006	0.16	0.019	0.48	0.031	0.78	0.080	2.04	1.89	2.81

#### COPYRIGHT

This document is protected under copyright law and is the property of Casmco Cable. Data contained herein is confidential to Casmco Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmco Cable or any affiliates without the prior written authorization of Casmco Cable.

#### CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmco Cable for dimensional verification, information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmco Cable is not responsible for any claim traceable to such error.

