

## CASPLAST™ UL/cUL

### Style 1571

-30°C to +80°C, 30V



#### Construction

**Type:** electrical wire

**Core:** bare or tin-plated copper

**Insulation:** extruded PVC

#### Production

**Range width:** AWG 30 to 10

**Options:** Please consult us for any special requirements

#### Application

**General use:** internal cabling for electrical or electronic appliances, computers, etc.



#### General characteristics

**Chemical behaviors:** good resistance to aggressive chemical environments

**Motion:** good resistance to alternate bending

#### Thermal characteristics

**Operating temperature:** -30°C to +80°C

#### Electrical characteristics

**Operating Voltage:** 30V

#### Approvals – Standards

**“Horizontal flame”:** as per UL approval

**UL approval:** as per standard UL 758

Casmoc Part No.	Wire gauge		Conductor structure		Conductor Diameter		Wall thickness		Final O.D.	
	(AWG)	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)
			(in)	(mm)						
11111301	10	105	0.010	0.254	0.118	3.00	0.014	0.35	0.146	3.70
11111302	12	65	0.010	0.254	0.094	2.40	0.014	0.35	0.122	3.10
11111303	14	19	0.015	0.374	0.074	1.88	0.014	0.35	0.102	2.58
11111304	16	26	0.010	0.254	0.059	1.50	0.014	0.35	0.083	2.10
11111305	18	16	0.010	0.254	0.046	1.17	0.012	0.30	0.069	1.75
11111306	20	21	0.007	0.18	0.037	0.95	0.010	0.25	0.057	1.45
11111307	22	17	0.006	0.16	0.030	0.76	0.010	0.25	0.050	1.26
11111308	24	11	0.006	0.16	0.024	0.61	0.010	0.25	0.043	1.10
11111309	26	19	0.004	0.10	0.020	0.50	0.010	0.25	0.039	1.00
		7	0.006	0.16	0.019	0.48	0.010	0.25	0.039	0.98
11111310	28	7	0.005	0.127	0.015	0.38	0.008	0.20	0.031	0.78
11111311	30	7	0.004	0.10	0.012	0.31	0.008	0.20	0.028	0.71



#### COPYRIGHT

This document is protected under copyright law and is the property of Casmoc Cable. Data contained herein is confidential to Casmoc Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmoc Cable or any affiliates without the prior written authorization of Casmoc Cable.

#### CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmoc Cable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmoc Cable is not responsible for any claim traceable to such error.