

## CASPLAST™ MC UL/cUL

### Style 2468

-30°C to +80°C, 300V



#### Construction

**Type:** multicore cable

**Core:** UL approved conductors with PVC insulation

**Insulation:** extruded PVC

**Sheath:** PVC

#### Production

**Range width:** AWG 26 to 16

**Options:** Please consult us for any special requirements

#### Application

**General use:** external or internal cabling for electrical appliances



#### General characteristics

**Chemical behaviors:** good resistance to aggressive chemical environments

#### Thermal characteristics

**Operating temperature:** -30°C to +80 °C

#### Electrical characteristics

**Operating Voltage:** 300V

#### Approvals – Standards

**“Horizontal flame”:** as per UL approval

**UL approval:** as per standard UL 758

Casmo Part No.	Wire gauge	Conductor structure			Conductor Diameter		Wall thickness		Final O.D.	
	(AWG)	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)
			(in)	(mm)						
11130401	16	26	0.010	0.254	0.059	1.50	0.016	0.40	0.094x0.193	2.40x4.90
		1	0.051	1.30	0.051	1.30	0.017	0.43	0.085x0.174	2.16x4.42
11130402	18	41	0.006	0.16	0.046	1.17	0.017	0.43	0.08x0.167	2.04x4.23
11130403	20	21	0.007	0.18	0.037	0.95	0.017	0.43	0.071x0.146	1.80x3.70
11130404	22	17	0.006	0.16	0.030	0.76	0.017	0.43	0.064x0.131	1.62x3.34
11130405	24	11	0.006	0.16	0.024	0.61	0.017	0.43	0.058x0.12	1.47x3.04
11130406	26	7	0.006	0.16	0.019	0.48	0.017	0.43	0.053x0.109	1.34x2.78
11130407	28	7	0.005	0.127	0.015	0.39	0.015	0.38	0.045x0.091	1.15x2.3



#### COPYRIGHT

This document is protected under copyright law and is the property of Casmocable. Data contained herein is confidential to Casmocable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmocable or any affiliates without the prior written authorization of Casmocable.

#### CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmocable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmocable is not responsible for any claim traceable to such error.