

CASTHERMCOAX™

Style RG178 FEP

-55°C to +200°C, 50 Ohms



Construction

Type: coaxial cable

Core: Silver Plated Copper Coated Steel (SPCCS)

Dielectric: FEP

Shielding: silver-plated copper braid

Sheath: FEP

Production

Standard: nominal diameter 1.83 mm

Options: Please consult us for any special requirements

Application

Aerospace and Defense: radio frequency communications, data transmission, wireless communication in extreme conditions

General characteristics

Operating environment: protection from electromagnetic interference

Chemical behavior: excellent resistance to chemical environments

Humidity: excellent resistance to humidity

Thermal characteristics

Operating temperature: -55°C to +200 °C

Electrical characteristics

Operating Voltage: 750V

Impedance: 50 Ohms

Approvals – Standards

Aeronautic and defense: MIL-DTL-17

Conductor structure			Conductor Diameter		Dielectric Diameter		Outer Shield Diameter		Final O.D.	
# Strands	Diam. Of Strands (mm)		(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
	(in)	(mm)								
7	0.004	0.1	0.012	0.3	0.035	0.88	0.051	1.3	0.072	1.83

DATA TRANSMISSION CHARACTERISTICS	
Impedance	50Ω
Capacitance max	96.45 pF / m
Use frequency max	3 GHz
Velocity of propagation	69.5%
Operating voltage	750V

SIGNAL ATTENUATION		
Frequency	Nominal attenuation	
(MHz)	(dB / 100 m)	(dB / 100 ft)
100	45.3	13.8
400	91.2	27.8
1000	146	44.5
3000	265	80.8



COPYRIGHT

This document is protected under copyright law and is the property of Casmocable. Data contained herein is confidential to Casmocable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmocable or any affiliates without the prior written authorization of Casmocable.

CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmocable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmocable is not responsible for any claim traceable to such error.