

## CASTHERMCOAX™

### Style RG316 U

-55°C to +200°C, 50 Ohms



#### Construction

**Type:** coaxial cable

**Core:** Silver Plated Copper Coated Steel (SPCCS)

**Dielectric:** PTFE

**Shielding:** silver-plated copper braid

**Sheath:** FEP

#### Production

**Standard:** nominal diameter 2.5 mm

**Options:** Please consult us for any special requirements

#### Application

**Aerospace and Defense:** radio frequency communications, data transmission, wireless communication in extreme conditions

#### General characteristics

**Operating environment:** protection from electromagnetic interference

**Chemical behavior:** excellent resistance to chemical environments

**Humidity:** excellent resistance to humidity

#### Thermal characteristics

**Operating temperature:** -55°C to +200°C

#### Electrical characteristics

**Operating Voltage:** 1200V

**Impedance:** 50 Ohms

#### Approvals – Standards

**Aeronautic and defense:** MIL-DTL-17

| Conductor structure |                       |       | Conductor Diameter |       | Dielectric Diameter |      | Outer Shield Diameter |      | Final O.D. |      |
|---------------------|-----------------------|-------|--------------------|-------|---------------------|------|-----------------------|------|------------|------|
| # Strands           | Diam. Of Strands (mm) |       | (in)               | (mm)  | (in)                | (mm) | (in)                  | (mm) | (in)       | (mm) |
|                     | (in)                  | (mm)  |                    |       |                     |      |                       |      |            |      |
| 7                   | 0.007                 | 0.175 | 0.021              | 0.525 | 0.060               | 1.52 | 0.077                 | 1.95 | 0.098      | 2.5  |

| DATA TRANSMISSION CHARACTERISTICS |              |
|-----------------------------------|--------------|
| Impedance                         | 50Ω          |
| Capacitance max                   | 96.45 pF / m |
| Use frequency max                 | 3 GHz        |
| Velocity of propagation           | 69.5%        |
| Operating voltage                 | 1200V        |

| SIGNAL ATTENUATION |                     |               |
|--------------------|---------------------|---------------|
| Frequency          | Nominal attenuation |               |
| (MHz)              | (dB / 100 m)        | (dB / 100 ft) |
| 100                | 26.2                | 8.0           |
| 400                | 53.1                | 16.2          |
| 1000               | 85.6                | 26.1          |
| 3000               | 153.2               | 46.7          |



#### COPYRIGHT

This document is protected under copyright law and is the property of Casmo Cable. Data contained herein is confidential to Casmo Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmo Cable or any affiliates without the prior written authorization of Casmo Cable.

#### CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmo Cable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmo Cable is not responsible for any claim traceable to such error.