


CASFLON™ 250 UL/cUL

Style1727
-65°C to +250°C, 600V



Construction

Type: electrical wire

Core: bare, tin-plated, nickel-plated, or silver-plated copper

Insulation: PFA

Production

Range width: AWG 32 to 10

Options: Please consult us for any special requirements

Application

General use: internal cabling for electrical appliances or electronic appliances

Industry: cabling for industrial machines

Electromechanics: cabling for rotating machines

Household appliances: cabling for household electrical heating appliances

General characteristics

Weather conditions: excellent resistance to UV

Chemical behaviors: excellent resistance to aggressive chemical environments

Humidity: excellent resistance to humidity

Mechanical behaviors: excellent mechanical strength

Thermal characteristics

Operating temperature: -65°C to +250 °C

Electrical characteristics

Operating Voltage: 600V

Test voltage: 2000 V

Approvals – Standards

“Horizontal flame”: as per UL approval

“FT1 flame rating”: as per UL approval

“VW-1 flame test”: as per UL approval

UL approval: as per standard UL 758

Casmocable Part No.	Wire gauge	Conductor structure			Conductor Diameter		Wall thickness		Final O.D.		Approx. Wt.	
	(AWG)	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb./kft)	(kg/km)
			(in)	(mm)								
1411001	10	37	0.017	0.43	0.119	3.01	0.020	0.51	0.16	4.03	41.80	62.20
1411002	12	19	0.019	0.49	0.096	2.45	0.020	0.51	0.14	3.47	28.10	41.82
1411003	14	19	0.015	0.37	0.073	1.85	0.020	0.51	0.11	2.87	18.70	24.40
1411004	16	19	0.012	0.3	0.059	1.5	0.020	0.51	0.10	2.52	13.30	16.40
1411005	17	19	0.010	0.26	0.051	1.3	0.020	0.51	0.09	2.32	11.95	14.80
1411006	18	19	0.009	0.23	0.045	1.15	0.020	0.51	0.09	2.17	10.60	13.10
1411007	20	19	0.007	0.19	0.037	0.95	0.020	0.51	0.08	1.97	7.71	11.47
		1	0.031	0.8	0.031	0.8	0.020	0.51	0.07	1.82	7.00	10.42
1411008	22	19	0.006	0.16	0.031	0.8	0.020	0.51	0.07	1.82	5.78	8.60
		1	0.026	0.65	0.026	0.65	0.020	0.51	0.07	1.67	5.03	7.49
1411009	24	7	0.008	0.2	0.024	0.6	0.020	0.51	0.06	1.62	4.49	6.68
		1	0.020	0.5	0.020	0.5	0.020	0.51	0.06	1.52	4.01	5.97
1411010	26	7	0.006	0.16	0.019	0.48	0.020	0.51	0.06	1.50	3.65	5.43
		1	0.016	0.4	0.016	0.4	0.020	0.51	0.06	1.42	3.27	4.87
1411011	28	7	0.005	0.12	0.014	0.36	0.020	0.51	0.05	1.38	2.92	4.35
		1	0.013	0.32	0.013	0.32	0.020	0.51	0.05	1.34	2.78	4.14
1411012	30	7	0.004	0.1	0.012	0.3	0.020	0.51	0.05	1.32	2.53	3.76
		1	0.010	0.254	0.010	0.254	0.020	0.51	0.05	1.274	2.47	3.68

COPYRIGHT

This document is protected under copyright law and is the property of Casmo Cable. Data contained herein is confidential to Casmo Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmo Cable or any affiliates without the prior written authorization of Casmo Cable


CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmo Cable for dimensional verification, information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmo Cable is not responsible for any claim traceable to such error.



CASFLON™ 250 UL/cUL

Style1727
-65°C to +250°C, 600V



Casmoc Part No.	Wire gauge	Conductor structure			Conductor Diameter		Wall thickness		Final O.D.		Approx. Wt.	
	(AWG)	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb./kft)	(kg/km)
			(in)	(mm)								
1411013	32	7	0.003	0.08	0.009	0.24	0.020	0.51	0.05	1.26	1.73	2.57
		1	0.008	0.20	0.008	0.2	0.020	0.51	0.05	1.22	1.68	2.50

COPYRIGHT

This document is protected under copyright law and is the property of Casmoc Cable. Data contained herein is confidential to Casmoc Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmoc Cable or any affiliates without the prior written authorization of Casmoc Cable.

CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmoc Cable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmoc Cable is not responsible for any claim traceable to such error.

