

CASLICON™ 150 UL/cUL

Style 3132
-60°C to +150°C, 300V



Construction

Type: electrical wire

Core: bare, tin-plated, nickel-plated, or silver-plated copper

Insulation: silicon rubber

Production

Range width: AWG 30 to 16

Options: Please consult us for any special requirements

Application

Lighting: cabling for household lighting appliances

Industry: industrial cabling in hot atmospheres

Electromechanics: cabling for rotating machines

Household appliances: cabling for household electrical heating appliances

General characteristics

Weather conditions: good resistance to UV

Operating environment: good resistance to thermal shock

Thermal characteristics

Operating temperature: -60°C to +150 °C

Electrical characteristics

Operating Voltage: 300V

Test voltage: 1500 V

Approvals – Standards

“Horizontal flame”: IEC 60754-2 / EN 60754-2

“FT1 flame rating”: as per UL approval

“VW-1 flame test”: as per UL approval

UL approval: as per standard UL 758

Casmocable Part No.	Wire gauge	Conductor structure			Conductor Diameter		Wall thickness		Final O.D.		Approx. Wt.	
	(AWG)	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb./kft)	(kg/km)
			(in)	(mm)								
3110101	16	7	0.020	0.5	0.059	1.5	0.015	0.39	0.090	2.28	10.31	15.34
3110102	17	32	0.008	0.2	0.053	1.34	0.015	0.39	0.083	2.12	8.60	12.79
3110103	18	7	0.016	0.4	0.047	1.2	0.015	0.39	0.078	1.98	6.88	24.40
3110104	20	7	0.013	0.32	0.038	0.96	0.015	0.39	0.069	1.74	4.77	16.40
3110105	22	7	0.010	0.26	0.031	0.78	0.015	0.39	0.061	1.56	3.40	14.80
3110106	24	7	0.008	0.2	0.024	0.6	0.015	0.39	0.054	1.38	2.49	13.10
3110107	26	7	0.006	0.16	0.019	0.48	0.015	0.39	0.050	1.26	1.89	2.81
3110108	28	7	0.005	0.12	0.014	0.36	0.015	0.39	0.045	1.14	1.45	2.16
3110109	30	7	0.004	0.1	0.012	0.3	0.015	0.39	0.043	1.08	1.06	1.58

COPYRIGHT

This document is protected under copyright law and is the property of Casmocable. Data contained herein is confidential to Casmocable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmocable or any affiliates without the prior written authorization of Casmocable.

CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmocable for dimensional verification, information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmocable is not responsible for any claim traceable to such error.



www.casmocable.com