

CASLICON™ 200 UL/cUL

Style 3530
-60°C to +150°C/200 °C, 600V



Construction

Type: electrical wire

Core: bare, tin-plated, nickel-plated, or silver-plated copper

Insulation: silicon rubber

Production

Range width: AWG 26 to 12

Options: Please consult us for any special requirements

Application

Lighting: industrial cabling in hot atmospheres

Industry: cabling for industrial machines

Electromechanics: cabling for rotating machines

Household appliances: cabling for household electrical heating appliances

General characteristics

Weather conditions: good resistance to UV

Operating environment: good resistance to thermal shock

Thermal characteristics

Operating temperature: -60°C to +150 °C /200 °C

Electrical characteristics

Operating Voltage: 600V

Test voltage: 2000 V

Approvals – Standards

“Horizontal flame”: IEC 60754-2 / EN 60754-2

“FT1 flame rating”: as per UL approval

“VW-1 flame test”: as per UL approval

UL approval: as per standard UL 758

Casmoc Part No.	Wire gauge	Conductor structure			Conductor Diameter		Wall thickness		Final O.D.		Approx, Wt.	
	(AWG)	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)	(lb./kft)	(kg/km)
			(in)	(mm)								
3210301	12	49	0.012	0.3	0.106	2.7	0.031	0.78	0.168	4.26	24.84	36.96
3210302	14	40	0.012	0.3	0.075	1.9	0.031	0.78	0.136	3.46	18.44	27.44
3210303	16	7	0.020	0.5	0.059	1.5	0.031	0.78	0.120	3.06	10.31	15.34
3210304	17	32	0.008	0.2	0.053	1.34	0.031	0.78	0.114	2.9	8.60	12.79
3210305	18	7	0.016	0.4	0.047	1.2	0.031	0.78	0.109	2.76	6.88	24.40
3210306	20	7	0.013	0.32	0.038	0.96	0.031	0.78	0.099	2.52	4.77	16.40
3210307	22	7	0.010	0.26	0.031	0.78	0.031	0.78	0.092	2.34	3.40	14.80
3210308	24	7	0.008	0.2	0.024	0.6	0.031	0.78	0.085	2.16	2.49	13.10
3210309	26	7	0.006	0.16	0.019	0.48	0.031	0.78	0.080	2.04	1.89	2.81

COPYRIGHT

This document is protected under copyright law and is the property of Casmoc Cable. Data contained herein is confidential to Casmoc Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmoc Cable or any affiliates without the prior written authorization of Casmoc Cable

CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmoc Cable for dimensional verification, information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmoc Cable is not responsible for any claim traceable to such error.



www.casmocable.com