



## CASTHERMCOAX™

### Style RG316 D

-55°C to +200°C, 50 Ohms



#### Construction

**Type:** coaxial cable

**Core:** Silver Plated Copper Coated Steel (SPCCS)

**Dielectric:** PTFE

**Shielding:** double silver-plated copper braid

**Sheath:** FEP

#### Production

**Standard:** nominal diameter 2.9 mm

**Options:** Please consult us for any special requirements

#### Application

**Aerospace and Defense:** radio frequency communications, data transmission, wireless communication in extreme conditions

#### General characteristics

**Operating environment:** protection from electromagnetic interference

**Chemical behavior:** excellent resistance to chemical environments

**Humidity:** excellent resistance to humidity

#### Thermal characteristics

**Operating temperature:** -55°C to +200°C

#### Electrical characteristics

**Operating Voltage:** 1200V

**Impedance:** 50 Ohms

#### Approvals – Standards

**Aeronautic and defense:** MIL-DTL-17

Conductor structure			Conductor Diameter		Dielectric Diameter		Outer Shield Diameter		Final O.D.	
# Strands	Diam. Of Strands (mm)		(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
	(in)	(mm)								
7	0.007	0.175	0.021	0.525	0.060	1.52	0.094	2.4	0.114	2.9

DATA TRANSMISSION CHARACTERISTICS	
Impedance	50Ω
Capacitance max	96.45 pF / m
Use frequency max	3 GHz
Velocity of propagation	69.5%
Operating voltage	120V

SIGNAL ATTENUATION		
Frequency (MHz)	Nominal attenuation	
	(dB / 100 m)	(dB / 100 ft)
100	26.2	8.0
400	53.1	16.2
1000	85.6	26.1
3000	153.2	46.7



#### COPYRIGHT

This document is protected under copyright law and is the property of Casmo Cable. Data contained herein is confidential to Casmo Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmo Cable or any affiliates without the prior written authorization of Casmo Cable

#### CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmo Cable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmo Cable is not responsible for any claim traceable to such error.