

CASUSTAN™ EV

FHLR91XC13X and FHLR4GC13X

-40°C to +150°C

Construction

Type: high voltage shielded automotive cable

Core: stranded bare copper

Insulation: 91X: XLPO for cables <6 mm²
4G: EVA for cables >6 mm²

Screen: tin-plated copper braid

Wrapping: tape

Sheath: TPE-E (Vulcanised Thermoplastic Elastomer 13X)

Production

Range width: 2.5 mm² - 150 mm²

Color: Orange

Application

Automotive: high voltage and high-temperature cables for e-mobility power applications

General characteristics

Operating environment: good resistance to thermal shock

Weather conditions: good resistance to UV

Chemical behaviors: good resistance to aggressive chemical environments

Humidity: excellent resistance to humidity

Mechanical behaviors: excellent flexibility

Thermal characteristics

Continuous operating temperature: -40°C to +150°C

Electrical characteristics

Operating Voltage: 1000 VAC / 1500 VDC

Test voltage: 10kV AC

Approvals – Standards

Automotive: ISO 6722-1 class D, ISO 19642-9 class D

Halogen free: IEC 60754-2 / EN 60754-2

FHLR91XC13X

Casmo Part No.	Conductor cross-section area		Conductor structure			Conductor Diameter		Insulation Diameter		Final O.D.		Linear core resistance at 20°C
	(AWG)	mm²	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)	
				(in)	(mm)							
8100501	14	2.5	50	0.010	0.26	0.08	2	0.11	2.85	0.20	5	7.6
8100502	12	4	56	0.012	0.31	0.10	2.5	0.14	3.55	0.23	5.8	4.71
8100503	10	6	84	0.012	0.31	0.12	3	0.16	4.15	0.26	6.6	3.14



COPYRIGHT

This document is protected under copyright law and is the property of Casmocable. Data contained herein is confidential to Casmocable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmocable or any affiliates without the prior written authorization of Casmocable.

CAUTION


The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmocable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmocable is not responsible for any claim traceable to such error.

CASUSTAN™ EV

FHLR91XC13X and FHLR4GC13X

-40°C to +150°C

FHLR4GC13X



Casmco Part No.	Conductor cross-section area		Conductor structure			Conductor Diameter		Insulation Diameter		Final O.D.		Linear core resistance at 20°C (Ω/ km)
	(AWG)	mm²	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)	
				(in)	(mm)							
8100601		8	60	0.016	0.41	0.15	3.8	0.20	5.05	0.30	7.6	2.38
8100602	8	10	78	0.016	0.41	0.17	4.3	0.23	5.75	0.33	8.4	1.82
8100603		12	92	0.016	0.41	0.19	4.7	0.24	6.1	0.35	8.9	1.52
8100604	6	16	126	0.016	0.41	0.21	5.4	0.27	6.9	0.38	9.7	1.16
8100605		20	154	0.016	0.41	0.24	6.2	0.30	7.6	0.42	10.6	0.955
8100606	4	25	189	0.016	0.41	0.26	6.7	0.32	8.2	0.44	11.2	0.743
8100607		30	224	0.016	0.41	0.29	7.4	0.36	9.1	0.48	12.1	0.647
8100608	2	35	273	0.016	0.41	0.31	7.9	0.38	9.7	0.50	12.7	0.527
8100609		40	301	0.016	0.41	0.33	8.5	0.41	10.4	0.54	13.6	0.473
8100610	1/0	50	385	0.016	0.41	0.37	9.4	0.45	11.5	0.59	14.9	0.368
8100611		60	294	0.020	0.51	0.42	10.6	0.50	12.6	0.63	15.9	0.315
8100612	2/0	70	360	0.020	0.51	0.46	11.6	0.54	13.7	0.67	17	0.259
8100613	4/0	95	480	0.020	0.51	0.53	13.5	0.64	16.2	0.78	19.9	0.196
8100614	250MCM	120	589	0.020	0.51	0.59	15.1	0.71	18	0.89	22.6	0.153
8100615	300MCM	150	741	0.020	0.51	0.67	17	0.79	20	0.98	24.9	0.122



COPYRIGHT

This document is protected under copyright law and is the property of Casmo Cable. Data contained herein is confidential to Casmo Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmo Cable or any affiliates without the prior written authorization of Casmo Cable.

CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmo Cable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmo Cable is not responsible for any claim traceable to such error.