

CASFLAM™ TGGT UL/cUL

Style 5256
+250 °C, 600V



Construction

Type: TGGT wire
Core: nickel-plated copper (2%), nickel-coated copper (27%), or pure nickel
Insulation: PTFE tape with glass serve
Reinforcing braid: varnished fiberglass braid

Production

Range width: AWG 24 to 8
Options: Please consult us for any special requirements

Application

Use : high-temperature appliances wiring material

General characteristics

Operating environment: good resistance to thermal shock
Chemical behavior: good resistance to oxidization

Thermal characteristics

Operating temperature: +250 °C

Electrical characteristics

Operating Voltage: 600V

Approvals – Standards

“FT1 flame rating”: as per UL approval
UL approval: as per standard UL 758
Other approval: RoHS Compliant

Casmocable Part No.	Wire gauge	Conductor structure				Wall thickness					Final O.D.		Approx. Wt.	
	(AWG)	# Strands	Diam. Of Strands		PTFE Tape		Fiberglass Serve		Fiberglass Braid		(in)	(mm)	(lb./kft)	(kg/km)
			(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)				
4310301	24	7	0.008	0.2	0.007	0.18	0.004	0.1	0.008	0.2	0.067	1.7	8.75	13.02
4310302	22	7	0.010	0.254	0.007	0.18	0.004	0.1	0.008	0.2	0.071	1.8	8.5	12.65
4310303	20	10	0.010	0.254	0.007	0.18	0.004	0.1	0.008	0.2	0.079	2.0	9.2	13.69
4310304	18	16	0.010	0.254	0.007	0.18	0.004	0.1	0.008	0.2	0.087	2.2	11	16.37
4310305	16	26	0.010	0.254	0.011	0.28	0.004	0.1	0.008	0.2	0.110	2.8	15	22.62
4310306	14	41	0.010	0.254	0.011	0.28	0.004	0.1	0.008	0.2	0.122	3.1	22	32.74
4310307	12	65	0.010	0.254	0.011	0.28	0.004	0.1	0.008	0.2	0.142	3.6	31	46.13
4310308	10	103	0.010	0.254	0.011	0.28	0.004	0.1	0.010	0.25	0.185	4.7	53	78.87
4310309	8	163	0.010	0.254	0.011	0.28	0.004	0.1	0.010	0.25	0.217	5.5	79	117.56
4310310	6	260	0.010	0.254	0.014	0.36	0.006	0.15	0.010	0.25	0.268	6.8	113	168.16
4310311	4	413	0.010	0.254	0.014	0.36	0.006	0.15	0.010	0.25	0.323	8.2	167	248.51
4310312	2	168	0.020	0.5	0.014	0.36	0.006	0.15	0.010	0.25	0.390	9.9	259	385.42

COPYRIGHT

This document is protected under copyright law and is the property of Casmo Cable. Data contained herein is confidential to Casmo Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmo Cable or any affiliates without the prior written authorization of Casmo Cable

CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmo Cable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmo Cable is not responsible for any claim traceable to such error.

