

CASPLAST™ MC UL/cUL

Style 20276

-30°C to +60 °C /80°C, 30V



Construction

Type: multicore cable

Core: UL approved conductors with PVC insulation

Insulation: extruded PVC

Sheath: PVC

Production

Range width: AWG 26 to 20

Options: Please consult us for any special requirements

Application

General use: external or internal cabling for electrical appliances



General characteristics

Chemical behaviors: good resistance to aggressive chemical environments

Thermal characteristics

Operating temperature: -30°C to +60 °C /80 °C

Electrical characteristics

Operating Voltage: 30V

Approvals – Standards

“FT1 flame rating” : as per UL approval

“Cable flame test” : as per UL approval

UL approval : as per standard UL 758

Casmoc Part No.	Cores	Wire gauge	Conductor structure			Insulation thickness		Shield Thickness		Sheath Thickness		Final O.D.	
		(AWG)	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)
				(in)	(mm)								
113070226	2	26	7	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.153	3.88
113070224		24	11	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.163	4.14
113070222		22	17	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.174	4.43
113070220		20	26	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.190	4.82
113070326	3	26	7	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.153	3.88
113070324		24	11	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.163	4.14
113070322		22	17	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.174	4.43
113070320		20	26	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.190	4.82
113070428	4	28	7	0.005	0.127	0.010	0.25	0.008	0.20	0.030	0.76	0.156	3.95
113070426		26	7	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.165	4.18
113070528	5	28	7	0.005	0.127	0.010	0.25	0.008	0.20	0.030	0.76	0.165	4.19
113070526		26	7	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.175	4.45
113070628	6	28	7	0.005	0.127	0.010	0.25	0.008	0.20	0.030	0.76	0.174	4.41
113070626		26	7	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.185	4.69
113070728	7	28	7	0.005	0.127	0.010	0.25	0.008	0.20	0.030	0.76	0.181	4.61
113070726		26	7	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.193	4.91
113070922	9	22	17	0.006	0.16	0.010	0.25	0.008	0.20	0.030	0.76	0.251	6.38



COPYRIGHT

This document is protected under copyright law and is the property of Casmoc Cable. Data contained herein is confidential to Casmoc Cable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmoc Cable or any affiliates without the prior written authorization of Casmoc Cable

CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmoc Cable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmoc Cable is not responsible for any claim traceable to such error.