

CASPLAST™ MC UL/cUL

Style 2468

-30°C to +80°C, 300V



Construction

Type: multicore cable

Core: UL approved conductors with PVC insulation

Insulation: extruded PVC

Sheath: PVC

Production

Range width: AWG 26 to 16

Options: Please consult us for any special requirements

Application

General use: external or internal cabling for electrical appliances



General characteristics

Chemical behaviors: good resistance to aggressive chemical environments

Thermal characteristics

Operating temperature: -30°C to +80 °C

Electrical characteristics

Operating Voltage: 300V

Approvals – Standards

“Horizontal flame”: as per UL approval

UL approval: as per standard UL 758

Casmocable Part No.	Wire gauge		Conductor structure		Conductor Diameter		Wall thickness		Final O.D.	
	(AWG)	# Strands	Diam. Of Strands		(in)	(mm)	(in)	(mm)	(in)	(mm)
			(in)	(mm)						
11130401	16	26	0.010	0.254	0.059	1.50	0.016	0.40	0.094x0.193	2.40x4.90
		1	0.051	1.30	0.051	1.30	0.017	0.43	0.085x0.174	2.16x4.42
11130402	18	41	0.006	0.16	0.046	1.17	0.017	0.43	0.08x0.167	2.04x4.23
11130403	20	21	0.007	0.18	0.037	0.95	0.017	0.43	0.071x0.146	1.80x3.70
11130404	22	17	0.006	0.16	0.030	0.76	0.017	0.43	0.064x0.131	1.62x3.34
11130405	24	11	0.006	0.16	0.024	0.61	0.017	0.43	0.058x0.12	1.47x3.04
11130406	26	7	0.006	0.16	0.019	0.48	0.017	0.43	0.053x0.109	1.34x2.78
11130407	28	7	0.005	0.127	0.015	0.39	0.015	0.38	0.045x0.091	1.15x2.3



COPYRIGHT

This document is protected under copyright law and is the property of Casmocable. Data contained herein is confidential to Casmocable and this document and/or any part of the data contained herein may not be copied, duplicated, or released for the manufacturing or sale of equipment outside of Casmocable or any affiliates without the prior written authorization of Casmocable.

CAUTION

The information included in this catalog is intended as a guideline only. For applications that require tight tolerances, please contact Casmocable for dimensional verification. Information herein is believed to be accurate as of the publication date; however, if an error exists it is unintentional and Casmocable is not responsible for any claim traceable to such error.